

Carrier **X²** 1800



Quietly delivering the next generation of reliability and performance in style.

PERFORMANCE SPECIFICATIONS

X² 1800



Condenser Dimensions

76.4" x 85.7" x 22.8"
(1,940 x 2,176 x 579 mm)

Evaporator Dimensions

66.3" x 45.2" x 8.2"
(1,684 x 1,149 x 280 mm)

Body Opening

66.8" x 46.0"
(1,696 x 1,168 mm)

Approximate Weight

1800: 1,625 lb. (737 kg)
Remote 50-gal. aluminum fuel tank: 65 lb. (29 kg)
Battery: 50 lb. (23 kg)

Cooling/Temperature Capacity:
Ambient at 100°F (38°C)
Speed: 1,700 rpm diesel

Evaporator Return Air Temp.	Diesel Operation	
	Btuh	Watts
35°F (2°C)	51,000	14,950
0°F (-18°C)	32,000	9,380
-20°F (-29°C)	18,500	5,420

X2 Series. The proven reliability and low-cost operation of the X Series platform engineered into a durable, sleek design.

- **Lower lifecycle cost** achieved by Extended Service Intervals (ESI™) and durable industry-leading engine, compressor, and microprocessor controller.
- **Bold, dramatic styling** features damage and dirt-resistant, colorfast composite doors.

Standard Features Include:

CT4-114TV diesel engine
1.9 liter indirect-injection
4 cylinders
15 qt. (14.2 liter) oil capacity
05G-37CFM compressor
37 CFM displacement
6 cylinders
High capacity oil pump
Refrigerant R-404A
UltraFresh 2™ temperature control
Automatic Start/Stop fuel saver
High-power 65-amp alternator
Remote aluminum fuel tank
50-gal. single-fill – 22"
Durashell 2™ composite doors
Single latch release
Automatic hot gas heating system
Pressurized coolant system
Automatic defrost control
TurboAir™ management system
Screw-post battery terminals
Microprocessor control system
Automatic pretrip
Self diagnostics
Digital function displays
ESI™ (Extended Service Interval) package
Multistage, synthetic media oil filter
Water-separating fuel filter
Heavy-duty, low-noise dry air cleaner
Extended-life antifreeze
Installation package

- **Best-in-class capacity and airflow** ensures dependable operation and optimum temperature control over a wide range of applications.
- **Quiet operation** features aero-acoustically designed grille and doors, coupled with extremely low RPM operation that also extends component life.
- **Fuel-efficient components** and refined microprocessor logic ensure lowest fuel use.

Accessories and Options:

DataTrak™ remote communications
Open door shutdown switches
Fuel heater
Synthetic engine oil
Evaporator drain line extensions
Silicone hoses
Remote light bar
Remote temperature probe
Stealth 2™ noise reduction package
Stud-post battery terminals
Unit impact protection bumpers
Microprocessor impact protection bumper
High-power 105-amp alternator
Extra-heavy-duty suction side fuel filter
Door locks
Chrome grille/stainless latch package
Custom color paint
Condenser bug/hail screen
DataLink™ data recorder
DataLink open door indicator switch
Flush-mount remote control panel
Remote aluminum fuel tanks:
30-gal. or 50-gal. single-fill – 18"
30-gal. or 75-gal. single-fill – 22"
100-gal. single- or double-fill – 22"
120-gal. single- or double-fill – 22"

X² 1800



North America
Carrier Transicold
700 Olympic Drive
Athens, GA 30601 USA
Tel: 706-357-7223
Fax: 706-355-5435

Mexico and Central America
Ejercito Nacional No. 418
Piso 9, Torre Yumal
Col. Chapultepec Morales
11570 Mexico, D.F.
Tel: (5255) 9126-0300
Fax: (5255) 9126-0383



Carrier

A United Technologies Company

Carrier Transicold Division
Carrier Corporation
Truck/Trailer Products Group
P.O. Box 4805
Syracuse, NY 13221 USA

www.trucktrailer.carrier.com