

Extreme performance and exceptional temperature control have never looked so good.

PERFORMANCE SPECIFICATIONS





2500A shown with chrome grille/stainless latch option

Condenser Dimensions 76.4" x 85.7" x 22.8"

(1,940 x 2,176 x 579 mm)

Evaporator Dimensions 66.3" x 45.2" x 8.2" (1,684 x 1,149 x 280 mm)

Body Opening 66.8" x 46.0" (1,696 x 1,168 mm)

Approximate Weight

2500A: 1,650 lb. (748 kg) Remote 50-gal. aluminum fuel tank: 65 lb. (29 kg) Battery: 50 lb. (23 kg)

Cooling/Temperature Capacity: Ambient at 100°F (38°C) Speed: 2,200 rpm diesel

Evaporator Return Air Temp.	Diesel Operation	
	Btuh	Watts
35°F (2°C) 0°F (-18°C) -20°F (-29°C)		19,345 10,845 7,330

X2 Series. Advanced

performance, dramatic styling, and lower noise. Built on the proven X-Series platform, 2500A establishes the world standard for durability and reliability.

- Sleek aerodynamics are designed into a durable and lasting door design that is manufactured from a high-strength composite.
- Advance[™] microprocessor with integrated DataLink[™] data recorder utilizes the industry's leading temperature control logic and cooling capacity while minimizing fuel use.

Standard Features Include:

CT4-134DI diesel engine 2.2 liter direct-injection 4 cylinders 15 qt. (14.2 liter) oil capacity 05G-41CFM compressor 41 CFM displacement 6 cylinders High capacity oil pump Refrigerant R-404A UltraFresh 3[™] temperature control Electronic stepper valve Automatic Start/Stop fuel saver High-power 65-amp alternator Remote aluminum fuel tank 50-gal. single-fill – 22" Durashell 2[™] composite doors Single latch release Automatic hot gas heating system Pressurized coolant system Automatic defrost control TurboAir™ management system Screw-post battery terminals Advance[™] microprocessor DatalLink[™] data recorder MessageCenter[™] display Multilingual display Advanced pretrip and diagnostics PCMCIA card interface ESI™ (Extended Service Interval) package Multistage, synthetic media oil filter Water-separating fuel filter

Heavy-duty, low-noise dry air cleaner Extended-life antifreeze Installation package

- Quieter operation achieved by aero-acoustic engineering of key components. The Stealth[™] option features exceptionally low levels of noise for additional driver comfort.
- Lower operating costs with Extended Service Interval (ESI[™]) components, advanced diagnostics, the most thorough pretrip available, and an industryleading warranty.
- **Preferred unit** of drivers, technicians, and fleet managers due to low noise, reliability, and lowest lifecycle cost.

Accessories and Options:

DataTrak[™] remote communications Open trailer door indicator and shutdown switches Fuel heater Synthetic engine oil Evaporator drain line extensions Silicone hoses Remote light bar Remote temperature probe Stealth 2[™] noise reduction package Stud-post battery terminals Unit impact protection bumpers Microprocessor impact protection bumper High-power 105-amp alternator Extra-heavy-duty suction side fuel filter Fuel tank level and shutdown sensor Door locks Chrome grille/stainless latch package Custom color paint Condenser bug/hail screen AutoFresh[™] air exchange IntelliSet[™] with ProductShield[™] Flush mount remote control panel Remote aluminum fuel tanks: 30-gal. or 50-gal. single-fill - 18" 30-gal. or 75-gal. single-fill - 22" 100-gal. single- or double-fill - 22" 120-gal. single- or double-fill - 22"





North America Carrier Transicold 700 Olympic Drive Athens, GA 30601 USA Tel: 706-357-7223 Fax: 706-355-5435
 Mexico and Central America

 Ejercito Nacional No. 418

 Piso 9, Torre Yurnal

 Col. Chapultepec Morales

 11570 Mexico, D.F.

 Tel: (5255) 9126-0300

 Fax: (5255) 9126-0383



A United Technologies Company

Carrier Transicold Division Carrier Corporation Truck/Trailer Products Group P.O. Box 4805 Syracuse, NY 13221 USA

www.trucktrailer.carrier.com

Specifications are subject to change without notice. ©2009 Carrier Corporation. A member of the United Technologies Corporation family. Stock symbol UTX. Warranty: Product warranty and limitations are outlined in Form 62-10695. This warranty applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Printed in USA 0109. Form 62-11367 Rev. A.